



## Data sheet for 1MT0013 Dust Explosion-proof Motors

### 1MT0013系列粉尘防爆电动机数据表

MLFB-Ordering data: 1MT0013-2AA43-3AA4

Explosion-proof grade: Ex tb IIIC T130°C Db



#### Motor type:

Client order no.:

Order no.:

Offer no.:

Remarks:

| U     | Δ / Y | f    | P       | P     | I     | n       | M    | NOM. EFF at ... load [%] |      |      | Power factor at ... load |      |      | I <sub>A</sub> /I <sub>N</sub> | M <sub>A</sub> /M <sub>N</sub> | M <sub>K</sub> /M <sub>N</sub> | IE-CL |
|-------|-------|------|---------|-------|-------|---------|------|--------------------------|------|------|--------------------------|------|------|--------------------------------|--------------------------------|--------------------------------|-------|
| [V]   |       | [Hz] | [kW]    | [hp]  | [A]   | [1/min] | [Nm] | 4/4                      | 3/4  | 2/4  | 4/4                      | 3/4  | 2/4  | I <sub>I</sub> /I <sub>N</sub> | T <sub>I</sub> /T <sub>N</sub> | T <sub>B</sub> /T <sub>N</sub> |       |
| 380   | Δ     | 50   | 30      | - / - | 55    | 2955    | 97   | 93.3                     | 93.4 | 92.5 | 0.89                     | 0.86 | 0.79 | 7.8                            | 2.4                            | 3.4                            | IE3   |
| 660   | Y     | 50   | 30      | - / - | 31.5  | 2955    | 97   | 93.3                     | 93.4 | 92.5 | 0.89                     | 0.86 | 0.79 | 7.8                            | 2.4                            | 3.4                            | IE3   |
|       |       |      |         |       |       |         |      |                          |      |      |                          |      |      |                                |                                |                                |       |
| IM B3 |       |      | FS 200L |       | 232kg | IP65    |      | IEC/EN 60034             |      |      | IEC, DIN, ISO, VDE, EN   |      |      |                                |                                |                                |       |

| Mechanical data / 机械性能数据                              |  |             | Terminal box / 接线盒                  |                 |
|---|--|-------------|-------------------------------------|-----------------|
| Sound pressure level 50Hz/60Hz<br>声压等级 50Hz/60Hz (负载) | 71 dB(A)   | - / -       | Terminal box position<br>接线盒位置      | top<br>顶部       |
| Moment of inertia<br>转动惯量                             | 0.133 kgm²   |             | Material of terminal box<br>接线盒材料   | cast iron<br>铸铁 |
| Bearing DE   NDE<br>轴承 DE   NDE                       | 6312 2RZ C3  | 6312 2RZ C3 | Type of terminal box<br>接线盒型号       | - / -           |
| Bearing lifetime<br>轴承寿命                              | - / -  |             | Gland size / Plug size<br>葛兰/闷盖尺寸   | M50x1.5/M50x1.5 |
| Lubricants<br>润滑油                                     | - / -  |             | Cable diameter<br>电缆直径(mm)          | 32-38           |
| Regreasing device<br>再润滑装置                            | No   |             | Max. auxiliary terminals<br>最大辅助端子数 | - / -           |
| Grease nipple<br>油杯                                   | - / -  |             | Auxiliary cable entry<br>辅助进线孔      | - / -           |
| Type of bearing<br>轴承类型                               | floating bearing DE<br>驱动端轴承浮动                         |             | Main terminal thread<br>主接线端子螺纹     | 6xM6            |
| Condensate drainage holes<br>排水孔                      | No   |             | Special design / 特殊设计               |                 |
| External earthing terminal<br>外部接地                    | Yes  |             |                                     |                 |
| Vibration class<br>振动等级                               | A  |             |                                     |                 |
| Insulation<br>绝缘等级                                    | 155(F)   |             |                                     |                 |
| Duty type<br>工作方式                                     | S1   |             |                                     |                 |
| Direction of rotation<br>旋转方向                         | bidirectional<br>双向                                    |             |                                     |                 |
| Frame material<br>机座材料                                | cast iron<br>铸铁  |             |                                     |                 |
| Data of anti condensation heating<br>防潮加热             | -/-  |             |                                     |                 |
| Coating<br>喷漆   | Yes  |             |                                     |                 |
| Color<br>颜色   | RAL7030  |             |                                     |                 |
| Motor protection<br>电机保护                              | - / -  |             |                                     |                 |
| Method of cooling<br>冷却方式                             | IC411 - self ventilated, surface cooled<br>IC411 - 自扇冷 |             |                                     |                 |

| Environmental conditions         |                 |
|----------------------------------|-----------------|
| Ambient temperature<br>环境温度      | -15 °C ~ +40 °C |
| Altitude above sea level<br>海拔高度 | 1000 m          |

Unrestricted

Technical data are subject to change! There may be discrepancies between calculated and rating plate values.

Page 1/1

Version:2022.01