



Data sheet for 1MT0013 Dust Explosion-proof Motors

1MT0013系列粉尘防爆电动机数据表

MLFB-Ordering data: 1MT0013-2DB03-3AA4

Explosion-proof grade: Ex tb IIIC T130°C Db



Motor type:

Client order no.:

Order no.:

Offer no.:

Remarks:

U	Δ / Y	f	P	P	I	n	M	NOM. EFF at ... load [%]			Power factor at ... load			I _A /I _N	M _A /M _N	M _K /M _N	IE-CL
[V]		[Hz]	[kW]	[hp]	[A]	[1/min]	[Nm]	4/4	3/4	2/4	4/4	3/4	2/4	I _I /I _N	T _I /T _N	T _B /T _N	
380	Δ	50	75	- / -	139	1485	482	95.0	95.3	94.8	0.86	0.82	0.73	7.6	2.8	3	IE3
660	Y	50	75	- / -	80	1485	482	95.0	95.3	94.8	0.86	0.82	0.73	7.6	2.8	3	IE3
IM B3			FS 280S		540kg	IP65		IEC/EN 60034			IEC, DIN, ISO, VDE, EN						

Mechanical data / 机械性能数据				Terminal box / 接线盒			
Sound pressure level 50Hz/60Hz 声压等级 50Hz/60Hz (负载)	66 dB(A)	- / -		Terminal box position 接线盒位置	top 顶部		
Moment of inertia 转动惯量	1.31 kgm ²			Material of terminal box 接线盒材料	cast iron 铸铁		
Bearing DE NDE 轴承 DE NDE	6317 C3	6317 C3		Type of terminal box 接线盒型号	- / -		
Bearing lifetime 轴承寿命	- / -			Gland size / Plug size 葛兰/闷盖尺寸	M63x1.5/M63x1.5		
Lubricants 润滑油	2# Li Grease			Cable diameter 电缆直径(mm)	37~44		
Regreasing device 再润滑装置	Yes			Max. auxiliary terminals 最大辅助端子数	- / -		
Grease nipple 油杯	M10x1			Auxiliary cable entry 辅助进线孔	- / -		
Type of bearing 轴承类型	floating bearing DE 驱动端轴承浮动			Main terminal thread 主接线端子螺纹	6xM10		
Condensate drainage holes 排水孔	No						
External earthing terminal 外部接地	Yes						
Vibration class 振动等级	A			Special design / 特殊设计			
Insulation 绝缘等级	155(F)						
Duty type 工作方式	S1						
Direction of rotation 旋转方向	bidirectional 双向						
Frame material 机座材料	cast iron 铸铁						
Data of anti condensation heating 防潮加热	-/-						
Coating 喷漆	Yes						
Color 颜色	RAL7030						
Motor protection 电机保护	- / -						
Method of cooling 冷却方式	IC411 - self ventilated, surface cooled IC411 - 自扇冷						

Environmental conditions	
Ambient temperature 环境温度	-15 °C ~ +40 °C
Altitude above sea level 海拔高度	1000 m

Unrestricted

Technical data are subject to change! There may be discrepancies between calculated and rating plate values.