

Data sheet for three-phase Squirrel-Cage-Motors

三相异步鼠笼电动机数据表

MLFB-Ordering data: 1TL8005-3BB53-3AA5



Motor type:

Client order no.:

Order no.:

Offer no.:

Remarks:

U	D / Y	f	P	P	I	n	M	NOM. EFF at ... load [%]			Power factor at ... load			IA/IN	MA/MN	MK/MN	IE-CL
[V]		[Hz]	[kW]	[hp]	[A]	[1/min]	[Nm]	4/4	3/4	2/4	4/4	3/4	2/4	II/IN	TI/TN	TB/TN	
380	D	50	280	/	495	1491	1793	97.4	97.7	97.6	0.88	0.85	0.77	8.5	2.5	3	IE5
660	Y	50	280	/	285	1491	1793	97.4	97.7	97.6	0.88	0.85	0.77	8.5	2.5	3	IE5
A = IM B3 / IM 100			FS 355L		1800 kg		IP55	IEC/EN 60034		IEC, DIN, ISO, VDE, EN							

Mechanical data / 机械性能数据			Terminal box / 接线盒	
Sound pressure level 50Hz/60Hz (No load)	76	/	Terminal box position	Right
Moment of inertia	5.62		Material of terminal box	Steel
Bearing DE NDE	6322 C3	6322 C3	Type of terminal box	/
Relubrication quantity (DE NDE)	60	60	Cable diameter	38-47
Relubrication interval (DE NDE)	4000		Max. cross-sectional area	/
Lubricants	BME		Main terminal thread	6xM16
Regreasing device	Yes		Cable gland	1 plug + 1 gland
Grease nipple	M10x1		Main cable entry	2xM72x2
Type of bearing	Fixed bearing on NDE		Special design / 特殊设计	
Condensate drainage holes	No			
External earthing terminal	Yes			
Vibration class	A			
Insulation	155(F) to 130(B)			
Duty type	S1			
Direction of rotation	bidirectional			
Frame material	Cast iron			
Data of anti condensation heating	No			
Coating	Yes			
Color	RAL 7011			
Motor protection	A = Without motor protection			
Method of cooling	IC411 - Self ventilated, surface cooled			
Environmental conditions / 环境条件				
Ambient temperature	-15	40		
Altitude above sea level	1000m			